

Oリング規格表

品番	太さ(W)	内径(ID)
S3	1.5 ±0.10	2.5
S4	1.5 ±0.10	3.5
S5	1.5 ±0.10	4.5
S6	1.5 ±0.10	5.5
S7	1.5 ±0.10	6.5
S8	1.5 ±0.10	7.5
S9	1.5 ±0.10	8.5
S10	1.5 ±0.10	9.5
S11.2	1.5 ±0.10	10.7
S12	1.5 ±0.10	11.5
S12.5	1.5 ±0.10	12.0
S14	1.5 ±0.10	13.5
S15	1.5 ±0.10	14.5
S16	1.5 ±0.10	15.5
S18	1.5 ±0.10	17.5
S20	1.5 ±0.10	19.5
S22	1.5 ±0.10	21.5
S22.4	2 ±0.10	21.9
S24	2 ±0.10	23.5
S25	2 ±0.10	24.5
S26	2 ±0.10	25.5
S28	2 ±0.10	27.5
S29	2 ±0.10	28.5
S30	2 ±0.10	29.5
S31.5	2 ±0.10	31.0
S32	2 ±0.10	31.5
S34	2 ±0.10	33.5
S35	2 ±0.10	34.5
S35.5	2 ±0.10	35.0
S36	2 ±0.10	35.5
S38	2 ±0.10	37.5
S39	2 ±0.10	38.5
S40	2 ±0.10	39.5